

.....

HFCU XRV-P

Recessed floor



29 dB(A) (2.20-2.80 kW)
extremely quiet
Air intake from bottom

200 mm | Maximum compactness for
flush-mounted installation

**The control must be
purchased as an accessory**

| Model | | | HFCU 226 XRV-P | HFCU 286 XRV-P | HFCU 366 XRV-P | HFCU 456 XRV-P | HFCU 566 XRV-P |
|--------------------------------------------|------------------|-------------------|---------------------------|----------------|----------------|----------------|----------------|
| Rated capacity | Cooling | kW | 2.20 | 2.80 | 3.60 | 4.50 | 5.60 |
| | Heating | kW | 2.40 | 3.20 | 4.00 | 5.00 | 6.30 |
| Electrical data | | | | | | | |
| Power supply | | Ph-V-Hz | 1-220~240V-50Hz | | | | |
| Electrical absorption | | W | 18 | 18 | 25 | 41 | 37 |
| Product Specifications | | | | | | | |
| Dimensions | LxHxD | mm | 915x470x200 | 915x470x200 | 915x470x200 | 1133x470x200 | 1253x566x200 |
| Net weight | | Kg | 16.5 | 16.5 | 17.8 | 20.9 | 24.6 |
| Sound power level ¹ | Max~Min | dB(A) | - | - | - | - | - |
| Sound pressure level at 1.4 m ¹ | Max~Min | dB(A) | 36~29 | 36~29 | 37~30 | 37~30 | 41~31 |
| Treated air volume ¹ | Max~Min | m ³ /h | 509~449 | 509~449 | 547~409 | 623~388 | 623~388 |
| Fan static pressure | Std/Max | Pa | 0/60 | 0/60 | 0/60 | 0/60 | 0/60 |
| Refrigerant connections | Liquid/Gas | mm (inch) | 6.35 (1/4") / 12.7 (1/2") | | | | |
| | Condensate drain | mm | 18.5 | 18.5 | 18.5 | 18.5 | 18.5 |
| Accessories | | | | | | | |
| Remote control | | | DHIR-5-6-XRV-K-P | | | | |
| Wired remote control | | | DHW-5-6-XRV-P | | | | |
| Optional parts | | | | | | | |
| Centralized control | | | DHC-8-64-XRV-P | | | | |

1. Values related to Max and Min speed of 7 levels settable by remote control.