

RESIDENTIAL AND COMMERCIAL R32

.....

ACTIVE LINE DC INVERTER MULTISPLIT INDOOR UNITS

Wall HKEU 203 ZL - HKEU 263-533-713 ZAL - HKEU 353 ZAL-1



Remote control included as standard

High density filter
Self-cleaning function
Anti-freeze function 8° C

Model			HKEU 203 ZL	HKEU 263 ZAL	HKEU 353 ZAL-1	HKEU 533 ZAL	HKEU 713 ZAL
Type	Indoor wall unit						
Control (included)	Remote control						
Rated capacity	Cooling	kW	2.10	2.60	3.50	5.30	7.00
	Heating	kW	2.30	2.90	3.80	5.60	7.30
Electrical data							
Power supply	Ph-V-Hz		-	-	-	-	-
Connection wires between I.U. and O.U.	no.		4	4	4	4	4
Refrigerant circuit							
Diameter of refrigerant piping on liquid/gas	mm (inches)		ø6.35(1/4") - ø9.52(3/8")	ø6.35(1/4") - ø9.52(3/8")	ø6.35(1/4") - ø9.52(3/8")	ø6.35(1/4") - ø12.74(1/2")	ø9.52(3/8") - ø15.88(5/8")
Product specifications							
Dimensions	LxDxH	mm	805x194x285	805x194x285	805x194x285	957x213x302	1040x220x327
Net weight		Kg	7.5	7.5	7.5	10	12.3
Sound pressure level	Hi/Mi/Lo/Ulo	dB(A)	40/30/26/21	40/30/26/21	40/34/26/22	44/37/30/25	44.5/42/34.5/28
Sound power level	Hi	dB(A)	54	54	53	55	59
Treated air (High / Med. / Low)		m ³ /h	520/460/340	520/460/340	600/500/360	840/680/540	980/817/662
Motor power (Output)		W	40	40	40	36	58
Optional parts							
Wi-Fi module			HKM-WiFi				
Wired remote control			NO				
Centralized control			NO				

MULTISPLIT INDOOR UNITS

Console HFUI 260 ZL - HFUI 350 ZAL



Remote control included as standard

4 air distribution inlets for increased system energy efficiency
Double air distribution mode
Anti-formaldehyde filter supplied

Model			HFUI 260 ZL	HFUI 350 ZAL
Type	Indoor console unit			
Control (included)	Remote control			
Rated capacity	Cooling	kW	2.70	3.50
	Heating	kW	3.50	3.80
Electrical data				
Power supply	Ph-V-Hz		-	-
Connection wires between I.U. and O.U.	no.		4	4
Refrigerant circuit				
Diameter of refrigerant piping on liquid/gas	mm (inches)		ø6.35(1/4") - ø9.52(3/8")	ø6.35(1/4") - ø9.52(3/8")
Product specifications				
Dimensions	LxDxH	mm	700x600x210	700x600x210
Net weight		Kg	14.8	14.8
Sound pressure level	Hi/Mi/Lo	dB(A)	43/41.5/35	43/41.5/35
Sound power level	Hi	dB(A)	58	58
Treated air (High / Med. / Low)		m ³ /h	512/480/370	512/480/370
Motor power (Output)		W	67	67
Optional parts				
Wi-Fi module			NO	
Wired remote control			YES	
Manual centralized control			YES	
	Requires NIM-GRH interface		XRV Mobile BMS	