

RESIDENTIAL AND COMMERCIAL R32

.....

MULTISPLIT INDOOR UNITS

Compact cassette 60x60 HTFU 260 ZL - HTFU 350-530 ZAL



Remote control included as standard

TFP 200 ZA panel with 360° air diffusion

Pre-set for external air inlet

Condensate drain pump with possibility of raising the discharge up to 750 mm from the lower height

Model	HTFU 260 ZL		HTFU 350 ZAL		HTFU 530 ZAL	
Type	Indoor cassette unit					
Control (included)	Remote control					
Rated capacity	Cooling	kW	2.60	3.50	5.30	
	Heating	kW	2.90	4.10	5.40	
Electrical data						
Power supply	Ph-V-Hz	-	-	-	-	
Connection wires between I.U. and O.U.	no.	4	4	4		
Refrigerant circuit						
Diameter of refrigerant piping on liquid/gas	mm (inches)	ø6.35(1/4") - ø9.52(3/8")		ø6.35(1/4") - ø9.52(3/8")		ø6.35(1/4") - ø12.74(1/2")
Product specifications						
Dimensions	LxDxH	mm	570x570x260	570x570x260	570x570x260	
Net weight		Kg	14.5	16.2	16.2	
Sound pressure level	Hi/Mi/Lo	dB(A)	38/33/29	41/37/34	44/42/41	
Sound power level	Hi	dB(A)	53	58	56	
Treated air (High / Med. / Low)		m ³ /h	580/500/450	617/504/415	680/560/500	
Motor power (Output)		W	45	45	45	
Accessories						
Decorative panel	TFP200ZA					
Optional parts						
Wi-Fi module	HKM-WIFI LCAC					
Wired remote control	YES					
Manual centralized control	YES ¹					
Wi-Fi centralized control	YES ¹					

1. Contact the Hokkaido technical department for installation.

MULTISPLIT INDOOR UNITS

Medium static pressure ducted

HUCU 260 ZL - HUCU 350-530 ZAL



Remote control included as standard

Compatible with systems **AIRZONE**

Optional Clean Air UV-kit purification device

Condensate drain pump with possibility of raising the discharge up to 750 mm from the lower height

Model	HUCU 260 ZL		HUCU 350 ZAL		HUCU 530 ZAL	
Type	Indoor ducted unit					
Control (included)	Remote control					
Rated capacity	Cooling	kW	2.60	3.50	5.30	
	Heating	kW	2.90	3.80	5.60	
Electrical data						
Power supply	Ph-V-Hz	-	-	-	-	
Connection wires between I.U. and O.U.	no.	4	4	4		
Refrigerant circuit						
Diameter of refrigerant piping on liquid/gas	mm (inches)	ø6.35(1/4") - ø9.52(3/8")		ø6.35(1/4") - ø9.52(3/8")		ø6.35(1/4") - ø12.74(1/2")
Product specifications						
Dimensions	LxDxH	mm	700x450x200	700x450x200	880x674x210	
Net weight		Kg	18	18	24.3	
Sound pressure level	Hi/Mi/Lo	dB(A)	40/34.5/27.5	40/34.5/27.5	41.5/38/33	
Sound power level	Hi	dB(A)	58	59	59	
Treated air (High / Med. / Low)		m ³ /h	500/340/230	600/480/300	880/650/350	
Fan static pressure	Std/Max	Pa	25/40	25/60	25/100	
Motor power (Output)		W	130	130	90	
Optional parts						
Wi-Fi module	HKM-WIFI LCAC					
Wired remote control	YES					
Manual centralized control	YES ¹					
Wi-Fi centralized control	YES ¹					

1. Contact the Hokkaido technical department for installation.