

PROJECT VRF R410A FULL DC INVERTER

.....

HFIU XRV-P Console



The control must be purchased as an accessory



210 mm deep | Ultra-compact design

Double air distribution mode: from above and/or below

7 fan speeds

Front and side air intake

Anti-formaldehyde filter | To eliminate the harmful effects of the gases released in rooms

Model	HFIU 225 XRV-P		HFIU 285 XRV-P		HFIU 365 XRV-P		HFIU 455 XRV-P	
Control (included)					none			
Rated cooling capacity	kW	2.20	2.80		3.60		4.50	
Rated heating capacity	kW	2.60	3.20		4.00		5.00	
Electrical data								
Power supply	Ph-V-Hz	1-220~240V-50Hz						
Electrical absorption	W	20	25		25		35	
Product specifications								
Air flow (1)	Max~Min	m ³ /h	430~229	510~229	510~229		660~400	
Sound pressure level at 1 m (1)	Max~Min	dB(A)	38~26	39~27	39~27		42~36	
Sound power level (1)	Max~Min	dB(A)	54~42		55~43		58~52	
Dimensions	LxHxD	mm	700x600x210					
Net weight		Kg	14		15			
Refrigerant connections	Liquid/Gas	Ø mm (inch)	6.35 (1/4") - 12.7 (1/2")					
Condensate drain		Ø mm	16					
Accessories								
Remote control			DHIR-5-6-XRV-K-P					
Wired remote control			DHW-5-6-XRV-K-P					
Optional parts								
Centralized control			see page 117					

(1) Values related to Max and Min speed of 7 levels settable by remote control.

HFCU XRV-P Recessed floor



The control must be purchased as an accessory



29 dB(A) (2.80 kW) | Extremely quiet

Air intake from bottom

212 mm | Maximum compactness for flush-mounted installation

Model	HFCU 285 XRV-P		HFCU 365 XRV-P		HFCU 565 XRV-P	
Control (included)					none	
Rated cooling capacity	kW	2.80		3.60		5.60
Rated heating capacity	kW	3.20		4.00		6.30
Electrical data						
Power supply	Ph-V-Hz	1-220~240V-50Hz				
Electrical absorption	W	45		55		88
Product specifications						
Air flow (1)	Max~Min	m ³ /h	569~421	624~375		1150~830
Fan static pressure	Std/Max	Pa		10/10		
Sound pressure level at 1 m (1)	Max~Min	dB(A)	36~29	37~30		41~31
Sound power level (1)	Max~Min	dB(A)	54~47	55~48		59~49
Dimensions	LxHxD	mm	840x545x212	1040x545x212		1340x545x212
Net weight		Kg	21	25.5		30.5
Refrigerant connections	Liquid/Gas	Ø mm (inch)	6.35 (1/4") - 12.7 (1/2")			
Condensate drain		Ø mm	16			
Accessories						
Remote control			DHIR-5-6-XRV-K-P			
Wired remote control			DHW-5-6-XRV-K-P			
Optional parts						
Centralized control			see page 117			

(1) Values related to Max and Min speed of 7 levels settable by remote control.